

CBM-262 Type II



CBM-262 Type II


F Features

- Two station printing
(Receipt and journal with paper winder)
- High-speed line thermal printing
- Paper auto loading
- Bar-code printing
- Cash drawer kick out
- Compatibility (ESC/POS)
- Page mode
- Auto cutter (Receipt only)

A Applications

- Receipt
- Journal
- Coupon
- Ticket
- Daily report
- Kitchen
- Delivery
- Bar-code

Mechanism



•LT-288

Specifications

Model	CBM-262 Type II
Printing method	Line thermal dot printing
Printing width	54mm, 432 dots
Printing speed	Max. 80mm/sec., 640 dot-line/sec. (Approx. 19 lines/sec.)
Number of columns	Font A: 36 columns Font B: 48 columns
Character size (W × H)	Font A: 1.25 × 3.00mm (12 × 24 dots) Font B: 0.88 × 2.13mm (9 × 17 dots)
Dot pitch	8 dots/mm (Horizontal/Vertical)
Bar-code type	UPC-A/E, JAN-13/8, Code 39, ITF, CODABAR, Code 93, Code 128
Line spacing	4.23mm (1/6 inch), can be set by a command (Min. 1/203 inch)
Paper	Thermal paper roll, 58mm × ø83mm
Interface	Parallel: Centronics Serial: RS-232C
Input buffer	8K bytes
Power supply voltage	Main unit: DC 24V
AC adapter	Input: AC 100-240V, 50/60Hz, 120V, Output: DC 24V, 1.8A
Weight	Main unit: 2.3kg, AC adapter: 0.4kg
External dimensions (W × D × H)	128 × 359.5 × 162.5mm
Operating temp. range	5 ~ 40°C
Storage temp. range	-10 ~ 60°C
Reliability	Head: 50,000,000 pulses or 50km Cutter: 300,000 cuts
Safety standard	UL, C-UL, FCC class A, TUV-GS, CE marking

Paper roll

58 mm

Type Classification

CBM-262II R F 230

① ② ③ ④

- ① Model type
262II: Tandem 2 station printer
- ② Interface
P: Parallel
R: Serial RS-232C
- ③ Character set
F: International
J: Japanese
- ④ Power source
100: 100 V
120: 120 V
230: 230 V

Further Information

Mechanism

LT-288

Auto Cutter

ACS-220
➔ 33P